

# ACCU-VENT

## Automatic Degassing Valves

### 2018 US Price List

#### Standard Features

- CPVC (Corzan) corrosion-resistant materials of construction on standard models
- Specially designed float material that automatically vents built-up gases on system start up and under working pressure
- Can be used on feed side or discharge side of pump (or both)
- Available in Stainless Steel for specific chemical, temperature, and pressure applications
- Also available in compact style, with ¼" connection

| Model         | Material | Bottom Connection      | Top Connection | Max. Temp.    | Max. Pressure | Price    |
|---------------|----------|------------------------|----------------|---------------|---------------|----------|
| AV-25-CPVC    | CPVC     | ¼" NPT or BSP Thread   | ¼" Thread      | 180 F (82 C)  | 150 PSIG      | \$99.00  |
| AV-50-CPVC    | CPVC     | ½" NPT or BSP Thread   | ½" Thread      | 180 F (82 C)  | 150 PSIG      | \$157.00 |
| AV-50-CPVC-S  | CPVC     | Socketweld             | ½" Thread      | 180 F (82 C)  | 150 PSIG      | \$157.00 |
| AV-75-CPVC    | CPVC     | ¾" NPT or BSP Thread   | ½" Thread      | 180 F (82 C)  | 150 PSIG      | \$157.00 |
| AV-75-CPVC-S  | CPVC     | Socketweld             | ½" Thread      | 180 F (82 C)  | 150 PSIG      | \$157.00 |
| AV-100-CPVC   | CPVC     | 1" NPT or BSP Thread   | 1" Thread      | 180 F (82 C)  | 150 PSIG      | \$195.00 |
| AV-25-PVDF    | PVDF     | ¼" NPT or BSP Thread   | ¼" Thread      | 180 F (82 C)  | 150 PSIG      | \$310.00 |
| AV-50-PVDF    | PVDF     | ½" NPT or BSP Thread   | ½" Thread      | 180 F (82 C)  | 150 PSIG      | \$586.00 |
| AV-75-PVDF    | PVDF     | ¾" NPT or BSP Thread   | ½" Thread      | 180 F (82 C)  | 150 PSIG      | \$689.00 |
| AV-50-316S/S  | 316 S/S  | ½" NPT or BSP Thread   | 1" Thread      | 500 F (260 C) | 250 PSIG      | \$266.00 |
| AV-75-316S/S  | 316 S/S  | ¾" NPT or BSP Thread   | 1" Thread      | 500 F (260 C) | 250 PSIG      | \$286.00 |
| AV-100-316S/S | 316 S/S  | 1" NPT or BSP Thread   | 1" Thread      | 500 F (260 C) | 250 PSIG      | \$315.00 |
| AV-150-316S/S | 316 S/S  | 1.5" NPT or BSP Thread | 1.5" Thread    | 500 F (260 C) | 250 PSIG      | \$668.00 |
| AV-200-316S/S | 316 S/S  | 2" NPT or BSP Thread   | 2" Thread      | 500 F (260 C) | 250 PSIG      | \$776.00 |

Contact our office for more information on product availability and applications. Other materials available upon request.

## Typical Installation

The installation below is a typical installation example only. Consult your engineering department for the appropriate installation for your application or call the factory for advice.

**Example: System arrangement for solenoid driven (above 150 psig) or motor driven pumps with highly recommended flooded suction conditions.**

