



HOW TO ORDER

ACCUDRAW® Calibration Cylinders

Sizing and Ordering Information:

Accudraw Standard Material of Construction

AC = All polypropylene construction – (see below for options)
 PV = All polyvinylchloride construction – (see below for options)

Example: AC#1-1000-B

AC = PP (polypropylene)
 1 = Bottom threaded conn. only
 1000 = 1000 ml
 B = BSP Thread

Note: Cylinders are NOT pressure vessels

e.g. Part # AC #1 - 1000 - B

Type:
 AC = Polypropylene
 PV = PVC

Std. connection is NPT threaded
Optional: add suffix as follows
 S = Socket weld connection (PVC only)
 B = BSPT Thread
 F = Flanged

Style:
 1 = Bottom threaded conn. only
 2 = Top/Bottom threaded conn
 3 = Bottom threaded conn. c/w removable vented dust cap
 4 = Top/Bottom threaded conn. c/w removeable "O" ring sealed top and float ring level indicator

Size:	Material
100 = 100 ml (1.6 GPH)	PP, PVC
250 = 250 ml (4 GPH)	PP, PVC
500 = 500 ml (8 GPH)	PP, PVC
1000 = 1000 ml (16 GPH)	PP, PVC
2000 = 2000 ml (32 GPH)	PP, PVC
4000 = 4000 ml (64 GPH)	PP, PVC
10000 = 10000 ml (160 GPH)	PVC
15000 = 15000 ml (240 GPH)	PVC
20000 = 20000 ml (320 GPH)	PVC

Custom sizes and materials available

Graduation Scale:
 PP Grad in ml only
 PVC Grad in ml/GPH

As Manufactured By:



PRIMARY FLUID SYSTEMS INC. Tel: (905) 333-8743
 Fax: (905) 333-8746
 North America Toll Free – 1-800-776-6580
 E-Mail: primary@primaryfluid.com
<http://www.primaryfluid.com>



HOW TO ORDER

ACCUDRAW® Glass Calibration Cylinders

Sizing and Ordering Information:

ACCUDRAW Standard Materials of Construction

- ACS** = All glass cylinder
- Polycarbonate outer tube
 - 304 Stainless steel hardware
 - Viton wetted "O" ring – (see below for options)
 - Buna outer sealing "O" ring

Example: ACS#2-1000-GKV-B

- ACS** = Glass
2 = Top/Bottom threaded connection
1000 = 1000 ml
GKV = Glass/PVDF/Viton construction
B = BSP Thread

Note: Cylinders are NOT pressure vessels

e.g. Part # **ACS #1 - 1000 - B**

Type:
ACS = Glass

Style:
2 = Top/Bottom threaded connection

Size:	Material
100 = 100 ml (1.6 GPH)	Glass
250 = 250 ml (4 GPH)	Glass
500 = 500 ml (8 GPH)	Glass
1000 = 1000 ml (16 GPH)	Glass
2000 = 2000 ml (32 GPH)	Glass
4000 = 4000 ml (64 GPH)	Glass
6000 = 6000 ml (95 GPH)	Glass
8000 = 8000 ml (127 GPH)	Glass
10000 = 10000 ml (160 GPH)	Glass
20000 = 20000 ml (320 GPH)	Glass

Custom sizes and materials available, please contact the factory for pricing and availability

Std. connection is NPT threaded
Optional: add suffix as follows

- GTV = Glass/PTFE/Viton construction
GKV = Glass/PVDF/Viton construction
GCV = Glass/CPVC(Corzan)/Viton construction
GSV = Glass/SS/Viton construction
B = BSPT Thread
F = Flanged
Substitute **E** for **V** for **EPDM** wetted "O" Ring seal

Graduation Scale:
Glass Grad in ml only

As Manufactured By:



PRIMARY FLUID SYSTEMS INC. Tel: (905) 333-8743
 Fax: (905) 333-8746
 North America Toll Free – 1-800-776-6580
 E-Mail: primary@primaryfluid.com
<http://www.primaryfluid.com>