



HOW TO ORDER

ACCUDRAW® Calibration Cylinders

Sizing and Ordering Information:

Accudraw Standard Material of Construction

AC = All polypropylene construction – (see below for options)
PV = All polyvinylchloride construction – (see below for options)

Example: AC#1-1000-B

AC = PP (polypropylene)
1 = Bottom threaded conn. only
1000 = 1000 ml
B = BSP Thread

Note: Cylinders are NOT pressure vessels

e.g. Part # **AC #1 - 1000 - B**

Type:

AC = Polypropylene
PV = PVC

Std. connection is NPT threaded Optional: add suffix as follows

S = Socket weld connection
(PVC only)
B = BSPT Thread
F = Flanged

Style:

1 = Bottom threaded conn. only
2 = Top/Bottom threaded conn.
3 = Bottom threaded conn. c/w
removable vented dust cap
4 = Top/Bottom threaded conn. c/w
removeable "O" ring sealed top
and float ring level indicator

Graduation Scale:

PP Grad in ml only
PVC Grad in ml/GPH

Size:

100	=	100 ml	(1.6 GPH)	PP, PVC
250	=	250 ml	(4 GPH)	PP, PVC
500	=	500 ml	(8 GPH)	PP, PVC
1000	=	1000 ml	(16 GPH)	PP, PVC
2000	=	2000 ml	(32 GPH)	PP, PVC
4000	=	4000 ml	(64 GPH)	PP, PVC
10000	=	10000 ml	(160 GPH)	PVC
15000	=	15000 ml	(240 GPH)	PVC
20000	=	20000 ml	(320 GPH)	PVC

Material

Custom sizes and materials available

As Manufactured By:



PRIMARY FLUID SYSTEMS INC. Tel: (905) 333-8743
Fax: (905) 333-8746
North America Toll Free – 1-800-776-6580

E-Mail: primary@primaryfluid.com

<http://www.primaryfluid.com>



HOW TO ORDER

ACCUDRAW® Glass Calibration Cylinders

Sizing and Ordering Information:

ACCUDRAW Standard Materials of Construction

ACS = All glass cylinder

- Polycarbonate outer tube
- 304 Stainless steel hardware
- Viton wetted "O" ring – (see below for options)
- Buna outer sealing "O" ring

Example: **ACS#2-1000-GKV-B**

ACS = Glass

2 = Top/Bottom threaded connection

1000 = 1000 ml

GKV = Glass/PVDF/Viton construction

B = BSP Thread

Note: Cylinders are NOT pressure vessels

e.g. Part # ACS #2 - 1000 - GKV - B

Type:

ACS = Glass

Style:

2 = Top/Bottom threaded connection

Std. connection is NPT threaded
Optional: add suffix as follows

B = BSPT Thread

F = Flanged

GTV = Glass/PTFE/Viton construction
GKV = Glass/PVDF/Viton construction
GCV = Glass/CPVC(Corzan)/Viton construction
GSV = Glass/SS/Viton construction
Substitute **E** for **V** for
EPDM wetted "O" Ring seal

Size:

			Material
100	=	100 ml (1.6 GPH)	Glass
250	=	250 ml (4 GPH)	Glass
500	=	500 ml (8 GPH)	Glass
1000	=	1000 ml (16 GPH)	Glass
2000	=	2000 ml (32 GPH)	Glass
4000	=	4000 ml (64 GPH)	Glass
6000	=	6000 ml (95 GPH)	Glass
8000	=	8000 ml (127 GPH)	Glass
10000	=	10000 ml (160 GPH)	Glass
20000	=	20000 ml (320 GPH)	Glass

Custom sizes and materials available, please
contact the factory for pricing and availability

Graduation Scale:

Glass Grad in ml only

As Manufactured By:



PRIMARY FLUID Tel: (905) 333-8743
SYSTEMS INC. Fax: (905) 333-8746

North America Toll Free – 1-800-776-6580

E-Mail: primary@primaryfluid.com

<http://www.primaryfluid.com>