

ACCU-VENT

Automatic Degassing Valves

2018 Canadian Price List

Standard Features

- CPVC (Corzan) corrosion-resistant materials of construction on standard models
- Specially designed float material that automatically vents built-up gases on system start up and under working pressure
- Can be used on feed side or discharge side of pump (or both)
- Available in Stainless Steel for specific chemical, temperature, and pressure applications
- Also available in compact style, with ¼" connection

| Model | Material | Bottom Connection | Top Connection | Max. Temp. | Max. Pressure | Price |
|----------------------|----------|------------------------|----------------|---------------|---------------|----------|
| AV-25-CPVC | CPVC | ¼" NPT or BSP Thread | ¼" Thread | 180 F (82 C) | 150 PSIG | \$120.00 |
| AV-50-CPVC | CPVC | ½" NPT or BSP Thread | ½" Thread | 180 F (82 C) | 150 PSIG | \$190.00 |
| AV-50-CPVC-S | CPVC | Socketweld | ½" Thread | 180 F (82 C) | 150 PSIG | \$190.00 |
| AV-75-CPVC | CPVC | ¾" NPT or BSP Thread | ½" Thread | 180 F (82 C) | 150 PSIG | \$190.00 |
| AV-75-CPVC-S | CPVC | Socketweld | ½" Thread | 180 F (82 C) | 150 PSIG | \$190.00 |
| AV-100-CPVC | CPVC | 1" NPT or BSP Thread | 1" Thread | 180 F (82 C) | 150 PSIG | \$240.00 |
| AV-25-PVDF | PVDF | ¼" NPT or BSP Thread | ¼" Thread | 180 F (82 C) | 150 PSIG | \$390.00 |
| AV-50-PVDF | PVDF | ½" NPT or BSP Thread | ½" Thread | 180 F (82 C) | 150 PSIG | \$710.00 |
| AV-75-PVDF | PVDF | ¾" NPT or BSP Thread | ½" Thread | 180 F (82 C) | 150 PSIG | \$834.00 |
| AV-50-316S/S | 316 S/S | ½" NPT or BSP Thread | 1" Thread | 500 F (260 C) | 250 PSIG | \$322.00 |
| AV-75-316S/S | 316 S/S | ¾" NPT or BSP Thread | 1" Thread | 500 F (260 C) | 250 PSIG | \$347.00 |
| AV-100-316S/S | 316 S/S | 1" NPT or BSP Thread | 1" Thread | 500 F (260 C) | 250 PSIG | \$382.00 |
| AV-150-316S/S | 316 S/S | 1.5" NPT or BSP Thread | 1.5" Thread | 500 F (260 C) | 250 PSIG | \$835.00 |
| AV-200-316S/S | 316 S/S | 2" NPT or BSP Thread | 2" Thread | 500 F (260 C) | 250 PSIG | \$970.00 |

Contact our office for more information on product availability and applications. Other materials available upon request.

Typical Installation

The installation below is a typical installation example only. Consult your engineering department for the appropriate installation for your application or call the factory for advice.

Example: System arrangement for solenoid driven (above 150 psig) or motor driven pumps with highly recommended flooded suction conditions.

